

sewage/effluent PUMPS

Flotec

Rugged, sewage and effluent pumps are capable of handling solids up to 2". Available in cast iron or engineered composite designs for a variety of wastewater applications. Tested and certified to SSPMA standards. Ideal for mound systems, leaching fields, effluent gravity sewers, laundry facilities, underground parking, grain storage and general dewatering.

FPSE3601A

1/2 HP

EXCLUSIVE full lifetime warranty

- Heavy-duty, rugged cast iron automatic submersible sewage pump
- Capable of handling 2" solids
- Maximum pumping capacity up to 9000 gallons per hour
- High efficiency motor with overload protection
- Includes by-pass float switch for automatic or manual operation
- 2" discharge meets standard code approvals
- 10' power cord for easy installation

FPSE3200A

4/10 HP

Better 1 year warranty

- Automatic submersible sewage pump
- Capable of handling 2" solids
- Maximum pumping capacity up to 5250 gallons per hour
- Durable, corrosion-resistant thermoplastic construction
- High efficiency motor with overload protection
- 2" discharge meets standard code approvals
- Includes 8' power cord

FPSE2800A

1/3 HP

Better 1 year warranty

- Automatic submersible effluent/dewatering pump
- Capable of handling 3/4" solids
- Maximum pumping capacity up to 3600 gallons per hour
- Thermoplastic construction
- High efficiency motor with overload protection
- Includes 15' power cord



PERFORMANCE INFORMATION

Rating	Warranty (years)	Model	HP	Type	Min. Sump Diameter	Performance - Gallons per Hour at Discharge Head in Feet						Maximum Lift (no flow)
						0'	5'	10'	15'	20'	25'	
EXCLUSIVE	LIFETIME	FPSE3601A	1/2	Sewage	18"	9000	7320	5400	2700	-	-	18 ft.
Better	1	FPSE3200A	4/10	Sewage	18"	5250	3900	2550	960	-	-	18 ft.
Better	1	FPSE2800A	1/3	Effluent	18"	3600	3180	2700	2100	1500	750	29 ft.